

## Flexiducting Ltd Stainless Steel Hose Products

### Ehaseflex Stainless Steel Braided Hose Connectors



Norminal Bore		Min. L	Max.L	Working Pressure	
Inches	mm	mm	mm	Bar	
1/2	15	150	1000	16	
3/4	20	150	1000	16	
1	25	150	1000	16	
1 1/4	32	150	1000	16	
1 1/2	40	150	1000	16	
2	50	150	1000	16	
2 1/2	65	150	1000	16	
3	80	150	1000	16	


Temperature: -276 to 700 Deg C.

Ehaseflex Flexible Stainless Steel Hose Assemblies are designed for connecting to rigid piping on suction or discharge sides to isolate vibration and movement from pumps, to help prevent damage from expansion and contraction, or to correct misalignment.

*Other sizes, lengths or working pressure available on request.*

#### Construction

Parts	Material	Type
Connections	SS316	150LB BSPT Male x BSP Female Swivel + Male Adapter Fitting are welded on to hose
Inner Core	SS316 Flexible Omega Annular Hose	
Outer Braid	SS316	



All Hoses are manufactured to ISO10380 and pressure tested

## Applications

- **Hot and Cold / Chilled Water Connectors**  
Suitable for potable and non-potable water applications
- **Gas Supply Connections**
- **Fan Coil Hoses**
- **Steam and Condensate Lines**
- **HVAC Hose Connections**
- **Fuel and Oil Lines**
- **Seismic Joints**

